

TALLER VERSION OF THE AQ-4000 MODEL

Same features, performance and options as an AQ-4000 but with increased chamber capacity and spray arms.

STANDARD FEATURES

Structural

- Double Wall Stainless Steel Chamber
- Stainless Steel Structural Frame
- Oscillating Stainless Steel Spray Arms
- Chamber Floor - Deck & Loading ramps
- Caster Wheels & Leveling Feet
- Seal Welded Wash Chamber
- Front Door - 12ga Stainless Steel
- Front Door Safety Window
- Disinfectant Application System
- Fill Line Temperature Gauge - 3" Dial

Controls & Electrical

- Programmable Logic Control Syst (PLC)
- 24 Volt DC Control System
- LCD Status Display
- Level Control - Self Diagnostics
- Wash Cycle Pressure Monitoring
- Non-Reset Cycle Counter
- GFCI Built in Circuit
- 230 Volt, 25 Amp, 50/60 Hertz SP

Cycles

- Variable Time Cycles (3, 5, or 7 min)
- Run Mode & Drain Mode Selection
- 'Clean Only', 'Clean & Apply Disinfectant' and 'Apply Disinfectant Only' cycles
- Automatic Chemical Injection
- Automatic Filling & Draining

Mechanical

- 3 HP Motor/Stainless Steel Pump

Wash System Nozzle Data

- Wash & Rinse System Nozzles: 78
- Disinfectant Nozzles: 36
- Wash PSI: 24
- Capacity Gallons/min: 114
- Capacity Gallons/cycle: 798
- Capacity Gallons/hour: 6840

Extras

- Fill & Drain Hose Set - 10' Each
- Loading Ramp Set (2 @ 48"L x 16"W)
- Indicate Door Swing(s) to fit your location



Aqua Phase Model shown with optional Disinfectant Mixing Station, Digital Temperature Display, Air Dry Blower, Lighted Wash Chamber, and Stainless Steel Control Panel Enclosure

OPTIONAL FEATURES & UPGRADES

- Lighted Wash Chamber
- Utility Wash Tray Set - Stainless Steel
- Digital Temperature Display
- Stainless Steel Control Panel Enclosure
- Pass-Through Design (Entry/Exit Doors)
- Conveyor Belt Transfer System
- Data Collections Computer System
- Fire Equipment/KEDS Wash Rack - Stainless Steel
- Chamber Swing Arms to wash Backboards
- Disinfectant Application Spray Wand (Exterior Mounted)
- Wash-Down Spray Gun & Hose (Exterior Mounted)
- Back Flow Prevention Devices / System
- Water Supply Temperature Mixing Valve (1/2" or 3/4" Line Size)
- Disinfectant Mixing Station (Exterior Mounted)
- Specialized Cycle Sequencing
- Air Dry Blower

DIMENSIONS & WEIGHT

Exterior

- Length: 98-7/16"
- Width: 65"
- Height: 100"

Chamber with Floor Deck

- Length: 93"
- Width: 40-1/4"
- Height: 73-7/8"

Crate/Pallet Dimensions

- Length: 112"
- Width: 72"
- Height: 108"

Approximate Shipping Weight

- 2800 lbs.
- 1270 Kilo

AQ-4102HT Door Opening Measurements: Width: 49-3/8" x Height: 93-1/2"

Once the Aqua Phase unit is in its location, all you need to do is hook up two hoses - one for the hot water fill line and one for the drain line. Then plug the Aqua Phase in an appropriate power source & begin saving time, improving efficiency & enhancing your infection control protocol.